

MS-315 PACKING

Packing made from PARA-ARAMIDA filaments impregnated with PTFE and lubricants. It has very high mechanical resistance, therefore installation instructions should be carefully followed in order to prevent pump shaft damage.

This packing is indicated for general services and it is specially designed for sugar and paper industry and for services with highly abrasive and viscous fluids, where the aramid's high mechanical resistance prevents wear at high working pressures.

This is a high quality universal packing used mainly in pumps and mixers under high responsibility conditions, though it can be used in a wide range of applications.

Please, follow carefully MONTERO's installation procedures.

Applications

• Packing for all kinds of equipment, pumps and valves ("ball", "globe" and "gate").

• Recommended by MONTERO for use In applications with abrasive fluids.

• For equipment in:

Refineries, Petrochemical and Chemical, Sugar and Paper Industry Thermal and Nuclear Power Generation Plants Steel Mills and Foundries Shipbuilding Industry Mining and Cement Industry Pharmaceutical and Process Industry



Ms 315		Ţ	S
Temperature (°C)	270		
Pressure (Bar)	250	75	35
Speed(m/s)	1,5	2	15
P-H	2-12		

Good performance and long service life of packings depend to a large extent on fitting and operation conditions, over which MONTERO FYE has no control. The data given on this technical sheet should not be used as application limits, but as a guidance for an appropriate choice. We can offer guarantees only for the quality of our products.

MONTERO FyE, S.A. Edificio Innobak

C/Ugartebeitia, nº 7 - 2ª Planta Dpto.8 48903 - BARAKALDO - BIZKAIA Email: access@monterofye.com www.monterofye.com