

## MF-360 GLANG PACKING

This packing is manufactured with high quality phenolic filaments –KYNOL NOVOLOID-vacuum impregnated with P.T.F.E. and special lubricant free of silicone.

This is a packing with low coefficient of friction, high flexibility and adaptability. It has an excellent performance to abrasive products and the filament has a high mechanical resistance to the temperature, steam and does not affect to the shafts. Even, it is combined with an excellent chemical resistance.




This is a high quality universal packing for uses in pumps and agitators in a high conditions but it can be used in a variety of applications.

This packing is specially recommended for pumps in high conditions and where the friction and the temperature affects to other type of packings making them lose their properties and not making the correct sealing.

### Applications

- Packing for every kind of equipments, pumps and “ball”, “globe” and “gate” valves.
- Recommended by MONTERO for use in agitators and centrifugal pumps of high applications.
- Equipment in:  
Refineries, Petrochemical and Chemical, Sugar and Paper Industry  
Thermal and Nuclear Power Generation Plants  
Steel Mills and Foundries  
Shipbuilding Industry  
Mining and Cement Industry  
Pharmaceutical and Process Industry



MF 360			
Temperature (°C)	270		
Pressure (Bar)	150	125	70
Speed (m/s)	2	3	9
P-H	1-13		