

MF-260 GLAND PACKING

This packing is manufactured from the highest quality of P.T.F.E. yarns having a high content of encapsulated graphite and lubricants.

The high content of graphite permits to work in high speed and the P.T.F.E., base of filaments, gives high chemical resistance. This packing has a high flexibility and adaptability. This packing is recommended for high speed equipments, as it has the lowest rate of coefficient of friction (P.T.F.E./GRAPHITE).




This packing permits to work in centrifugal pumps, valves and alternative movement equipments, also in mixers, agitators, and in general in every kind of equipmet. This packing can be considered as a universal except for hard oxidants , like; nitric acid and alcaline melted materials.

This packing is specially recommended for centrifugal pumps and high speed equipments.

Applications

- Packing for every kind of equipments, pumps and valves.
- Recommended by MONTERO for use in centrifugal equipments and agitators. Equipments with low coefficient of friction.
- Equipment in:
Refineries, Petrochemical and Chemical , Sugar and Paper Industry
Thermal and Nuclear Power Generation Plants
Steel Mills and Foundries
Shipbuilding Industry
Mining and Cement Industry
Pharmaceutical and Process Industry



MF 260			
Temperature (°C)	270		
Pressure (Bar)	250	250	20
Speed (m/s)	2	3	25
P-H	0-14		